



General Product Specifications

Eureka **Opal FS SRS3** & Jindara **Riverina FS SRS2**

Dimensions and Specifications	
Overall Dimension (Height)	800 mm
Overall Dimension (Width)	650 mm
Overall Dimension (Depth)	508 mm
Firebox Dimension (Height)	297 mm
Firebox Dimension (Width)	440 mm
Firebox Dimension (Depth)	282 mm
Door Opening Dimension (Height x Width)	200 x 490mm
Glass Viewing Size (Height x Width)	223 x 456mm
Flue Size	150mm
Back of Heater to Flue Centre	180 mm
Shipping weight	132kg
Linings	Firebricks on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements	
Min. Hearth Width	890 mm
Min. Hearth Depth	960 mm
Min. Hearth Thickness	12 mm
Min. In Front Of Unit	400 mm
Rear Clearance	125mm*
Side Clearance	325 mm
Corner Clearance	150 mm
	* denotes standard flue shield required (included in wood heater)
Emissions and Efficiency	
Emissions	0.9g/kg
Efficiency	69%*
Peak Output	14kw
	*Peak efficiency % quoted
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	