



# General Product Specifications

Eureka Pearl FS & Jindara Tilga FS

Dimensions and Specifications	
Overall Dimension (Height)	765 mm
Overall Dimension (Width)	690 mm
Overall Dimension (Depth)	548 mm
Firebox Dimension (Height)	362 mm
Firebox Dimension (Width)	522 mm
Firebox Dimension (Depth)	432 mm
Door Opening Dimension (Height x Width)	256 x 522mm
Glass Viewing Size (Height x Width)	285 x 570mm
Flue Size	150mm
Back of Heater to Flue Centre	205 mm
Shipping weight	203kg
Linings	Cast Iron Liners on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements (Perforated outer flue kit)	
Min. Hearth Width	945 mm
Min. Hearth Depth	895 mm
Min. Hearth Thickness	9 mm
Min. In Front Of Unit	300 mm
Rear Clearance	50mm*
Side Clearance	325 mm
Corner Clearance	75mm*
	* denotes standard flue shield required (included in wood heater)
Hearth & Clearance requirements (Solid outer flue kit)	
Min. Hearth Width	945 mm
Min. Hearth Depth	1000 mm
Min. Hearth Thickness	9 mm
Min. In Front Of Unit	300 mm
Rear Clearance	155 mm
Side Clearance	325 mm
Corner Clearance	50 mm



# General Product Specifications

Eureka Pearl FS & Jindara Tilga FS

Emissions and Efficiency	
Emissions	0.9g/kg
Efficiency	80%*
Peak Output	16kw
	*Peak efficiency % quoted
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	