



General Product Specifications

Eureka **Amber FS** & Jindara **Townsend FS**

Dimensions and Specifications	
Overall Dimension (Height)	730 mm
Overall Dimension (Width)	640 mm
Overall Dimension (Depth)	502 mm
Firebox Dimension (Height)	360 mm
Firebox Dimension (Width)	538 mm
Firebox Dimension (Depth)	292 mm
Door Opening Dimension (Height x Width)	285 x 420 mm
Glass Viewing Size (Height x Width)	270 x 410 mm
Flue Size	150 mm
Back of Heater to Flue Centre	176 mm
Shipping weight	163 kg
Linings	Firebricks on walls and base
Baffle thickness	8mm Lower Baffle, 6mm Upper Baffle
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements (Perforated outer flue kit)	
Min. Hearth Width	820 mm
Min. Hearth Depth	1060 mm
Min. Hearth Thickness	24 mm
Min. In Front Of Unit	550 mm
Rear Clearance	250mm*
Side Clearance	750 mm
Corner Clearance	500mm, or 350mm**
	* denotes 900mm, 180 deg flue shield required
	**denotes side wing kit to be fitted (purchased separately)
Hearth & Clearance requirements (Half Shield flue kit)	
Min. Hearth Width	820 mm
Min. Hearth Depth	1060 mm
Min. Hearth Thickness	24 mm
Min. In Front Of Unit	550 mm
Rear Clearance	300 mm
Side Clearance	825 mm
Corner Clearance	475mm, or 300mm**
	**denotes side wing kit to be fitted (purchased separately)