



# General Product Specifications

Eureka **Opal Inbuilt SRS4** &  
Jindara **Riverina Inbuilt SRS3**

Dimensions and Specifications	
Overall Dimension (Height)	750 mm
Overall Dimension (Width)	882 mm
Fascia Depth	42 mm
Rear Casing Dimension (Height)	595 mm
Rear Casing Dimension (Width)	570 mm
Rear Casing Dimension (Depth)	365 mm
Firebox Dimension (Height)	297 mm
Firebox Dimension (Width)	440 mm
Firebox Dimension (Depth)	282 mm
Door Opening Dimension (Height x Width)	200 x 490mm
Glass Viewing Size (Height x Width)	223 x 456mm
Flue Size	150mm
Back of Fascia to Flue Centre	232 mm
Shipping weight	118kg
Linings	Firebricks on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance Requirements	
Min. Hearth Width	890 mm
Min. Hearth Depth (in front of unit)	530 mm
Min. Hearth Thickness	12 mm
Clearance to Mantle Upright	50 mm
Clearance to Mantel Shelf (from appliance base)	1100 mm
Clearance to Mantel Breast Plate (from appliance base)	1040 mm
Emissions and Efficiency	
Emissions	0.9g/kg
Efficiency	72%*
Peak Output	14kw
	*Peak efficiency % quoted
<p>CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION</p>	