



General Product Specifications

Eureka Pearl Inbuilt & Jindara Tilga Inbuilt

| Dimensions and Specifications | | |
|--|---|--|
| | Masonry Insert | Zero Clearance Insert |
| Overall Dimension (Height) | 640 mm | 674 mm |
| Overall Dimension (Width) | 855 mm | 850 mm |
| Fascia Depth | 16 mm | 3 mm |
| Rear Casing Dimension (Height) | 595 mm | N/A - See Zero Clear- |
| Rear Casing Dimension (Width) | 751 mm | N/A - See Zero Clear- |
| Rear Casing Dimension (Depth) | 484 mm | N/A - See Zero Clear- |
| Firebox Dimension (Height) | 362 mm | |
| Firebox Dimension (Width) | 522 mm | |
| Firebox Dimension (Depth) | 432 mm | |
| Door Opening Dimension (Height x Width) | 256 x 522mm | |
| Glass Viewing Size (Height x Width) | 285 x 570mm | |
| Flue Size | 150mm | |
| Back of Fascia to Flue Centre | 326 mm | N/A - See Zero Clearance Install Guide |
| Shipping weight | 162kg | 256kg |
| Linings | Cast Iron Liners on walls | |
| Baffle thickness | 8mm | |
| Glass Type | Flat, toughened 5mm ceramic | |
| Hearth & Clearance Requirements | | |
| Min. Hearth Width | 945 mm | |
| Min. Hearth Depth (in front of unit) | 550 mm | |
| Min. Hearth Thickness | 18 mm | |
| Clearance to Mantle Upright | 55 mm | |
| Clearance to Mantel Shelf (from appliance base) | 1500mm* | |
| Clearance to Mantel Breast Plate (from appliance base) | 1410 mm | |
| | * denotes mantle deflector required (included in wood heater) | |
| Emissions and Efficiency | | |
| Emissions | 1.0g/kg | |
| Efficiency | 74%* | |
| Peak Output | 12kw | |
| | *Peak efficiency % quoted | |
| CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION | | |